


Coating Data Sheet



Designation

Coating type description OLD	PU
Coating type description NEW	PU 55

Design

Coating Material	Polyurethane (thermoplastic)
Colour	Yellow
Surface pattern	Smooth (sanded)

Technical data

Hardness [Shore(A)]	55
Density [kg/m ³]	
Coating thickness min. [mm]	2.0
Coating thickness max. [mm]	10.0
d factor *	20
Minimum pulley diameter D _{min} (approx.) [mm]	[d factor] x [selected belt thickness]
Minimum operating temperature [°C]	-10
Maximum operating temperature [°C]	70

Coefficient of static friction

against PE foil	0.34
against wood	0.51
against sheet glass	0.55
against cardboard	0.55
against aluminium	0.47
against steel sheet	0.56

Coating Data Sheet

Properties

Electrostatic properties	non-conductive
Wear resistance	medium
Compressibility	No
Product release properties	good release
Cleanability	good

Chemical resistance

General chemical resistance to	Generic fats and oils
--------------------------------	-----------------------

Special Fabrication

Sanding	Yes
Milling	Yes
Punching	Yes

Applications

Paper / Cardboard conveying, Feeder & haul-off belts
in cable industry, General conveying

General remarks

High chemical resistance in general. Good release properties.