

Coating Data Sheet



Designation

Coating type description OLD	U20/LG; PU foil LG
Coating type description NEW	PU 85/LG

Design

Coating Material	Polyurethane (thermoplastic)
Colour	Transparent
Surface pattern	Longitudinal groove profile

Technical data

Hardness [Shore(A)]	85
Density [kg/m ³]	
Coating thickness min. [mm]	2.0
Coating thickness max. [mm]	4.0
d factor *	30
Minimum pulley diameter D _{min} (approx.) [mm]	[d factor] x [selected belt thickness]
Minimum operating temperature [°C]	-20
Maximum operating temperature [°C]	80

Coefficient of static friction

against PE foil	1.15
against wood	0.89
against sheet glass	1.31
against cardboard	0.80
against aluminium	1.28
against steel sheet	1.30

Coating Data Sheet

Properties

Electrostatic properties	non-conductive
Wear resistance	high
Compressibility	No
Product release properties	medium
Cleanability	effortful

Chemical resistance

General chemical resistance to	Generic fats and oils
--------------------------------	-----------------------

Special Fabrication

Sanding	No
Milling	No
Punching	Yes

Applications

Glass conveying, General conveying, Conveying of abrasive goods

General remarks

High chemical and abrasion resistance in general.